



Model 2370-120v Specifications

DUST CONTROL HIGH SPEED BURNISHER

Feature		English / Metric
Pad Drive System		
Motor volts		120 V
Motor amps		15 amp
Motor power		1.5 hp/ 1.1 kW
Motor type		Direct drive, permanent magnet DC, circuit breaker protected
Pad diameter		20-inch/ 508 mm
Pad driver description		Flexible disc w/ centering lock, free floating motor, accommodates uneven floors
Pad speed burnishing		2000 rpm @ full load (15 amps)
Sound rating		66 dBa
Chassis & Handle Const	ruction	
Chassis design		Rotationally-molded medium density polyethylene
Handle design		Injection molded handle w/ metal tube. Hand trigger grip operation w/ dual safety lock. Fold over for storage.
Productivity		
Maximum coverage Rate per hour		10,000 ft²/ 929 m²
Machine Dimensions		
Length		32.5-inch / 825 mm
Machine Width		22.5-inch / 570 mm
Height		47.5-inch / 1205 mm
Weight Without cord With cord		80 lb / 36 kg 92 lb / 42 kg
Dirt/ Debris Recovery Sy	stem	
Dust control system		Built-in dust collection system
Filter description		Cloth filter bag (std), filters w/ 98% efficiency @ 0.1 micron
Power cord		
Power cord length		900-inch/ 22860 mm
Power cord type		14 gauge, 3-wire, ST
Warranty	3 YEARS/2500 HOURS PARTS AND LABOR. NO TRAVEL. 10 YEARS ON ROTATIONALLY-MOLDED POLYETHYLENE TANKS. PLEASE CALL FOR MORE WARRANTY INFORMATION	