

Product Specifications

FEATURES	SPECIFICATIONS*			
	H1	C2	H2	H5
Product Name				
Solution System				
Solution Tank Capacity	15 gal (57 L)			
Solution Pump Amps	1.0A	1.6A		2.5A
Solution Pump Voltage	115V			120V
Solution Pump Pressure	120 psi (8.3 bar)	220 psi (15.2 bar)	220 psi (15.2 bar)	50-500 psi (3.45-34 bar)
Solution Pump Flow Rate	0.8 gpm (3.03 L/min)			
Solution Hose Dimensions	15 ft (5 m) x .25 in (6.4 mm)			
In-line Heater Watts	1000 Watts	-	1750 Watts	
In-line Heater Amps	14A	-	14A	
In-line Heater Temperature	200° F max	-	140° F low/ 200° F max high	
Recovery System				
Recovery Tank Capacity	13.5 gal (51 L)			
Recovery Hose Dimensions	15 ft (5 m) x 1.5 in (38 mm)			
Vacuum Motor	.685 HP (.51 kW), 3-Stage			.342 HP (.26 kW), 3-Stage
Vacuum Amps	13.2A			6.5A
Water lift/Air flow	137 in (3480 mm)			155 in (3937 mm)
Maximum Vacuum Airflow	107 cfm (3.0 m ³ /min)			90 cfm (2.55 m ³ /min)
Power System				
Circuit Locator	-		Yes	
Power Cord Plug Type	NEMA 5-20R	NEMA 5-15P		
Power Cord Length	40 ft (12 m)			
Power Cord Configuration	Single Cord		Dual Cord	
System Voltage	120V / 60 HZ			
Total Power Consumption, Dual Plug	-	-	26.5A	25.7A
Total Power Consumption, Single Plug**	20A	15A	15A each	
Machine Specifications				
Length	32.5 in (826 mm)			
Width	25.25 in (641 mm)			
Height	41.5 in (1054 mm)			
Weight	110 lbs (50 kg)	102 lbs (46 kg)	100 lbs (45 kg)	132 lbs (60 kg)
Shipping Weight	160 lbs (73 kg)	152 lbs (69 kg)	160 lbs (73 kg)	185 lbs (84 kg)
Sound level (operator's ear)	>70 dBA	75 dBA	75 dBA	>68 dBA
Accessories				
Standard Wand/Tool	Stainless Steel			Titanium
Optional Wand	Titanium			-
Optional Hose Length	25 ft (8 m) x 1.5 in (38 mm)			
Approvals				
CRI	Gold w/ Titanium Wand	Gold w/ Titanium Wand	Gold w/ Titanium Wand	Gold w/Titanium Wand Platinum w/ Orbio
ETL (US/C)	Yes	Yes	Yes	Yes

*Specifications are subject to change. **Plug circuit max.