

# Portable Spot Extractor



**Clean spots before they become stains with the portable spot extractor.**

### Just the right tool

The spot extractor conveniently cleans smaller areas and is perfect for use on spills and upholstery cleaning, auto detailing and many other other applications.

### Durable tools

Metal hand tool and optional metal floor tool help reduce maintenance cost by outlasting their plastic counterparts.

### Complete spotting solution

Add the optional rolling cart and chemical kit and have everything you need at your fingertips for cleaning spots.



### Key Benefits

- Perfect for cleaning small spots on carpet, upholstery and many other applications
- Durable metal hand tool with see-through window to ensure complete recovery
- Easily fill/dump the spotter in multiple locations such as sinks, tubs and others



# Portable Spot Extractor



Features	Specifications*	
<b>Product Name</b>	EX-SPOT-8	220 V
<b>Vacuum System</b>		
Airflow at orifice	80 cfm / 2.26 m <sup>3</sup> /hr	84.5 cfm / 2.39 m <sup>3</sup> /hr
Vacuum motor amps	7 A	3.5 A
Vacuum motor HP	1.12 hp / .84 kW	
Vacuum motor stages	2 stage	
Vacuum motor type	Peripheral discharge, bypass: 4.8 / 122 mm diameter, recognized by UL	
Vacuum motor voltage	120 V	220 V
Vacuum motor watts	840 watts	770 watts
Water lift at sealed orifice	71 in / 1803.4 mm	77.5 in / 1968.5 mm
<b>Recovery System</b>		
Recovery tank wet capacity	1.5 gal / 5.67 L	
Vacuum hose length	8 ft / 2.43 m	
<b>Pump System</b>		
Solution pump amps	1.25 A	.75 A
Solution pump pressure	30 psi / 2.07 bar	
Solution pump voltage	120 V	220 V
Solution pump watts	150 watts	165 watts
<b>Solution Delivery System</b>		
Solution capacity	2 gal / 7.57 L	
Solution flow rate	0.25 gpm / 0.95 L/min	
Solution hose description	clear braided hose	
Solution hose length	8 ft / 2.43 m	
Solution pump watts	150 watts	
Spray jets count	1 jet	
<b>Chassis and Body Construction</b>		
Chassis and Body Construction	White, translucent, rotationally-molded polyethylene	
Metal parts coating	White epoxy powder coating or zinc plating	
<b>Power System</b>		
Power cord length	25 ft / 7.62 m	
Power cord type	SJTO: recognized by UL and CSA, non-marking safety yellow with grounded plug	
Power consumption amps	8.25 A	4.1 A
Power consumption voltage	120 V	220 V
Power consumption watts	990 watts	902 watts
<b>Dimensions/Accessories</b>		
Length/Width/Height/Net Weight	L: 21 in / 553.4 mm, W: 7.75 in / 196.8 mm, H: 17.5 in / 444.5 mm, Wt: 18 lb / 8.2 kg	
Standard Accessories	4 in / 100 mm metal window hand tool and 8 ft / 2.4 m vacuum and solution hoses	
<b>Warranty</b>	See your sales representative or authorized distributor for complete warranty details.	

\*Specifications subject to change without notice

Note: All 120V models will come with a dual Tennant/Nobles decal