



T20 Specifications | Industrial Rider Scrubber

SCRUBBING SYSTEM

Cleaning path		
Cylindrical main brushes	40 in	1,020 mm
Disk main brushes	42 in	1,070 mm
With scrubbing side brush	54 in	1,370 mm
With sweeping side brush (cylindrical only)	56 in	1,420 mm
Cylindrical main brushes		
Brush speed	480 rpm	
Brush diameter (2)	12 in	300 mm
Brush down pressure (up to)	390 lb	177 kg
Disk main brushes		
Brush speed	230 rpm	
Brush diameter (3)	14 in	360 mm
Brush down pressure (up to)	400 lb	181 kg
Disk side brush		
Brush speed	150 rpm	
Brush diameter – scrubbing	16 in	410 mm
Brush diameter – sweeping (cylindrical only)	21 in	533 mm
Tanks		
Solution tank	80 gal	303 L
Solution capacity with ES [®]	125 gal	473 L
Recovery tank	95 gal	360 L
Demisting chamber	15 gal	57 L
Debris tray (cylindrical only)		
Volume capacity	1.1 ft ³	31 L
Weight capacity	110 lb	50 kg
Vacuum fan		
Speed	11,000 rpm	
Water lift	35 in	890 mm

PROPELLING SYSTEM

Propel speed forward (variable up to)	8.0 mph	12.9 km/h
Propel speed reverse (variable up to)	3.0 mph	4.8 km/h
Engine-gasoline		
Gross Intermittent Power*	50.7 hp / 37.8 kW	@2800 rpm
Tennant Governed Power	40.6 hp / 30.3 kW	@2300 rpm
Engine-LPG (2.0 L)		
Gross Intermittent Power*	51.6 hp / 38.5 kW	@2800 rpm
Tennant Governed Power	42.4 hp / 31.6 kW	@2300 rpm
Moteur Diesel (1.5 L)		
Gross Intermittent Power*	24.8 hp / 18.5 kW	@2300 rpm
Tennant Governed Power	24.8 hp / 18.5 kW	@2300 rpm
Gradeability		
Transport at gross weight	10.0 deg	/ 18.0%
Working (cleaning)	8.0 deg	/ 14.0%
Ground clearance (transport)	3 in	80 mm
Tire front (1), solid	18 x 5.5 in	460 x 140 mm
Tires rear (2), solid	16 x 3.5 in	410 x 90 mm

MACHINE DIMENSIONS

Length	95 in	2,410 mm
Width		
Frame	50 in	1,270 mm
Rear squeegee	51 in	1,300 mm
With side brush	58 in	1,473 mm
Height		
With overhead guard	83.5 in	2,120 mm
Weight		
Empty	3,300 lb	1,497 kg
GVW	4,900 lb	2,223 kg
Minimum aisle turn	110 in	2,790 mm

STANDARD FEATURES

- 1-Step™ one button scrub operation
- Touch-n-Go™ wheel-mounted module
- Wheel-mounted horn
- Wheel-mounted water shut-off
- No-tool squeegee change
- No-tool brush change
- Yellow maintenance touch points
- Demisting chamber
- Dura-Track™ parabolic squeegee
- Cushion rollers
- Fire extinguisher
- SmartRelease™ breakaway squeegee system
- Headlights and LED taillights w/ back-up alert
- High-density Duramer™ exterior
- MaxPro™ hydraulic technology
- Underwriter's Laboratory (UL) certified

OPTIONAL EQUIPMENT

- Pro-Panel™ controls
- ec-H2O™ solution system
- ES[®] Extended Scrub w/detergent metering
- AV backup alarm (LED)
- Fire extinguisher
- Flashing warning light
- Overhead guard
- Vacuum wand (wet pick-up)
- Safety warning light
- Side Brush - Edge cleaning for scrubbing or sweeping
- Spray hose – 15 ft / 5 m w/ cleanout tool
- Squeegee protection kit
- Squeegee vacuum wand
- Strobing warning light
- Pressure washer (2200 psi) with 25 ft (7.0 m) hose
- IRIS[®] solution**
- Underwriters Laboratory (UL[®]) Type LPS Certified

WARRANTY

Please refer to your local Tennant representative for information.

For a complete selection of genuine Tennant brushes and pads, please consult the *T20 Parts and Consumables Reference Guide*.

*Per SAE J1995

**Available in select regions