

TENNAL TE

T681

Small Ride-On Scrubber

Big Productivity in a Small Rider

Small size design, intuitive controls with large display delivers versatile operation to provide excellent performance and efficient cleaning. The T681 is ideal for cleaning large spaces in areas such as retail stores, hospitals and schools.



Clean Effectively, Longer

Clean more productively and continuously with large volume solution/recovery tanks, integrated chemical dosing system helping reduce possible over/under scrubbing, as well as indicator controls alerting when the solution & recovery tanks are full.



Simple Operation

Ease of training and quick startup using one-button cleaning operation that lowers the scrub head and squeegee at the same time.



Chem-Dose System

Ensure consistent and correct chemical usage with integrated chemical dosing system for continuous operation and cost savings.

Inside the T681

- Simple operation with adjustable cleaning settings with a large easy-to-use control panel.
- Enhance facility
 image and safety by
 recovering more water
 with high-performance
 3-stage vacuum motor.
- 3. Effectively scrub across different surface levels with automatic scrub head level adjustment.

- Reduce maintenance time by easily accessing service areas with removable panels.
- 5. Consistent water pick-up with durable "V" shaped squeegee design and standard Linatex® squeegee blades.
- **6. Simple no-tools** brush change system.



T681 Specifications

FEATURE	SPECIFICATION
Cleaning path	32 in / 850 mm
Productivity (per hour) theoretical max	54,605.3 ft²/hr /5,073 m²/h
Estimated coverage (per hour)*	33,981. 7 ft²/h / 3,157 m²/h
Scrubbing speed	3.7 mph / 6.0 kmh
Scrub head and squeegee raise/lower	independent actuators
Brush/pad speed	200 rpm
Brush/pad pressure	up to 132.3 lbs / 60 kg
Solution tank capacity	26.4 gal / 100 L
Recovery tank capacity	29.1 gal / 110 L
Battery run time - up-to hours**	2.4
Battery voltage	24V (4 x 6V)
Dimensions (LxWxH)	59.6 in x 42.91 x 48.81 in / 1,504 x 1,090 x 1,240 mm
Squeegee width	42.91 in / 1,090 mm
Weight (with heaviest battery)	950.2 lbs / 431 kg
External radius (wall to wall)	77.2 in / 1,960 mm
Maximum climbing angle	16%
Sound level (operator's ear)***	75 dB
Chem-Dose tank capacity	1.3 gal / 5 L

Specifications subject to change without notice.

For a demonstration or additional information, call +1.800.553.8033 or email info@tennantco.com

Tennant Company

10400 Clean Street Eden Prairie, MN 55344-2650, USA

USA/Canada: +1.800.553.8033 Quebec: +1.800.361.9050 Overseas: +1.763.540.1315

www.tennantco.com | info@tennantco.com

^{*} Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.

^{**} Run times are based on Continuous Scrubbing Run Times.

^{***} Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA