

# T7 Micro-Rider Floor Scrubber

## Easy Operation & Maintenance

Clean both large areas and tight spaces easily with a floor scrubber designed for greater efficiency and less environmental impact.

## Available Technologies



ec-H2O NanoClean®



IRIS® Asset Manager



**Easily train** new operators to use the simple, intuitive controls.



**Leave behind no cleaning solution** even around 180-degree turns, with the T7's equal-pressure, parabolic squeegee.



**"No hassle" squeegee system**, there are no tools for maintenance and the blade is factory set at the optimum recovery angle.

# More T7 Features

- 1. Exclusive Hygenic® solution and recovery tanks** are fully accessible for easy cleaning.
- 2. Decrease the chance of accidents** with automatic braking and parking brake actuation.
- 3. Quickly** remove and replace brushes and squeegees.
- 4. Choose either** disk for smooth floors without debris or cylindrical for capturing light debris.



## T7 Specifications

FEATURE	SPECIFICATION		
	26 in/660 mm	28 in/710 mm	32 in/810 mm
Productivity (per hour) Theoretical Max	45,760 ft <sup>2</sup> / 4,250 m <sup>2</sup> (disk)	49,280 ft <sup>2</sup> / 4,578 m <sup>2</sup> (cylindrical)	56,320 ft <sup>2</sup> / 5,230 m <sup>2</sup> (disk) 56,320 ft <sup>2</sup> / 5,230m <sup>2</sup> (cylindrical)
Estimated Coverage* Conventional	23,760 ft <sup>2</sup> / 2,210 m <sup>2</sup> (disk)	25,740 ft <sup>2</sup> / 2,391 m <sup>2</sup> (cylindrical)	29,700 ft <sup>2</sup> / 2,760 m <sup>2</sup> (disk) 29,700 ft <sup>2</sup> / 2,760 m <sup>2</sup> (cylindrical)
Estimated Coverage*ec-H2O NanoClean®	31,680 ft <sup>2</sup> / 2,950 m <sup>2</sup> (disk)	30,030 ft <sup>2</sup> / 2,790 m <sup>2</sup> (cylindrical)	39,600 ft <sup>2</sup> / 3,680 m <sup>2</sup> (disk) 34,650 ft <sup>2</sup> / 3,219 m <sup>2</sup> (cylindrical)
Brush motor		.6 hp / 0.45 kW (disk) 0.75 hp / 0.5 kW (cylindrical)	
Brush/pad RPM		225 rpm (disk) 1,500 rpm (cylindrical)	
Brush/pad pressure		80, 120, 160 lb / 36, 54, 73 kg (disk) 40, 80, 120 lb / 18, 36, 54 kg (cylindrical)	
Solution tank capacity		29 gal / 110 L	
Recovery tank capacity		29 gal / 110 L	
Vacuum motor		0.6 hp / 0.45 kW	
Vacuum waterlift		70 in / 1,780 mm	
System voltage		24 volt	
Battery run time (up to hours)**		3.0	
Length x width x height	60 x 33.25 x 50 in 1,520 x 850 x 1,270 mm	60 x N/A x 50 in 1,520 x N/A x 1,270 mm	60 x 39.25 x 50 in 1,520 x 1,000 x 1,270 mm
Weight (with Batteries)		850 lb / 386 kg	
Sound level (operator's ear)***		67 dBA (disk) 69 dBA (cylindrical)	

Specifications subject to change without notice and will vary throughout the operation of the machine; averages are shown.

For a demonstration or additional information,  
call **+1.800.553.8033** or email **info@tennantco.com**