



Model T2 Specifications

BATTERY-POWERED WALK-BEHIND SCRUBBER-DRYER

Feature	
Scrubbing System	
Cleaning Path	43 cm / 17 in. – Pad Assist
Solution Tank Capacity	26 liter / 6.9 gal.
Productivity (Per Hour)	
Theoretical Max	1,900 m ² / 20,230 ft ²
Estimated Actual	672 m ² / 7,234 ft ²
Variable Solution Flow Rate	0-1.1lpm / 0-.3 gpm
Brush Motor	.75 kW / 1 hp
Brush Operating Speed	230 rpm
Maximum Brush / Pad Pressure	23 kg / 50 lbs.
Recovery System	
Recovery Tank Capacity	36 liter / 9.5 gal. – fully accessible and cleanable (Includes demisting chamber)
Vacuum Fan	
Motor	0.30 kW / 0.4 hp
Stages	2
Vacuum Motor (Maximum)	1.84 cubic mm/minute / 65cfm
Sealed Water Lift	102 cm / 40 in.
Squeegee Description	69.5 cm / 27.4 in. curved squeegee assembly with quick-change four sided rear blade
Drive System	
Caster Description	70 mm / 2.75 in. diameter polyurethane
Wheel Description	178 x 38 mm / 7 in. x 1.5 in. non-marking polyurethane
Batteries (12V system)	
Optional Lead Acid / Run time	(2) 12V, 85 AH / Up to 2 hours
Optional Gel / Run time	(4) 12V, 70 AH / Up to 1.75 hours
Optional Lead Acid/Run time	(2) 12V, 72 AH / Up to 1.75 hours (EU Only)
Dimensions / Weight / Sound level	
Length	112 cm / 44.1 in.
Width	
Body	44.1 cm / 17.4 in.
Scrub head	47.8 cm / 18.8 in.
Squeegee	69.5 cm / 27.4 in.
Height Maximum (Handle Lowest Position)	93 cm / 36.6 in.
Height Adjustable Handle - Range	12.6 cm / 5 in.
Net Weight	
Less Batteries	80 kg / 176 lbs.
With Batteries (2) 12V 70 AH gel	136 kg / 300 lbs.
Minimum Aisle Turn:	122 cm / 48 in.
Sound Level	68 dBa
Warranty	24 months (or max 2000 running hours) on parts and 12 months (or max 1000 running hours) on labour, which ever comes first, excluding wear items