# T600 E Battery-Powered Walk-Behind Scrubber



An industrial-strength, walk-behind scrubber designed to provide **high-performance** results, reduce costs to clean and enhance facility image.



Type E and EE trucks are tested by ETL and listed to operate in classified locations as defined in the National Fire Protection Association's NFPA 505.

### **KEY BENEFITS**

The T600 EE walk-behind scrubber is ideal for some special hazardous environments.

- Tennant is the only company that has a listed Type EE battery-powered floor cleaning machine.
- UL 583 Type EE battery-powered floor scrubbers have electrical equipment completely enclosed.
- Type EE battery-powered machines are usually mandated by the Authority Having Jurisdiction (AHJ) for use in a hazardous (classified) location.

### **POSSIBLE APPLICATIONS**

 The T600 EE is intended for use in hazardous environments that are involved in the production, handling, processing and storage of hazardous materials such as perfumes, cosmetics, paints, printing inks, pharmaceuticals and rubbers.\*

### **CONFIGURATION**

### **T600 EE CONFIGURATION**

- 800mm disc scrub head
- Pro-Membrane<sup>™</sup> control panel
- 240 AH batteries only
- Off-board charger or without charger only
- Polyurethane tires

### **OPTIONS**

- Manual battery watering
- Polyurethane Hose (Oil Resistant) w/Drain Control Valve
- Parking brake
- Pneumatic or foam filled tires
- Transport kit/ accessory clip

Note: The following are not available on this machine: ec-H2O NanoClean®, Severe Environment™, rinse hose with spray nozzle and Smart-Fill™.

\*It is the responsibility of the user to determine the suitability for use in the hazardous (classified) locations.

# **SPECIFICATIONS**

MACHINE SPECIFICATIONS	ACHINE SPECIFICATIONS	
Length	1671 mm	
Width	856 mm	
Height	1107 mm	
GVW	593 kg	

BRUSH DRIVE SYSTEM	
Scrub Motor	2 x 36 VDC, .6 HP brush motor/ 0.45 kW
Brush Pad RPM	300 RPM
Brush Down Pressure	Low: 45 kg Medium: 68 kg High:90 kg

	SOLUTION/RECOVERY SYSTEM	
	Solution Tank Capacity	121 L
	Recovery Tank Capacity	140 L
	Vacuum Motor	36 VDC, 1.3 hp / 1 kW 30 A

BATTERY SYSTEM	
Battery Type -6 required	Standard: Wet 240AH

## T600 EE - APPROVALS (U.S./CANADA ONLY)

ETL Listed to UL 583 Type EE









TO CLEAN

MAINTAIN HEALTH

ENHANCE FACILITY

EASE OF OPERATION