

# Floor Scrubbers

Reliable floor scrubbers that offer a simple, straightforward ownership experience at the right price.

## 416S

14IN / 35CM MICRO WALK-BEHIND SCRUBBER



Maneuverable to scrub in difficult to reach spaces



Simple and comfortable to operate



Large tank capacity in small size machine



## 1040S

20IN / 50CM WALK-BEHIND SCRUBBER



Maneuverable, with easy-to-use pad assist operation



Solution control with automatic stop



Robust construction in a compact scrubber



Self-leveling brush for maximum cleaning performance



## 1870S

24/28IN, 60/70CM WALK-BEHIND SCRUBBER



Easy to maneuver with forward and reverse self-propel



Solution control with automatic stop



Durable construction in a mid-size scrubber



Self-leveling brush with high RPM for maximum cleaning efficiency



## 2180SR

20IN / 50CM MICRO-RIDER FLOOR SCRUBBER



Quickly reach many areas of a facility with a ride-on scrubber



Compact design easily fits into most congested areas



Simple to operate control panel with visual display



Quiet operation allows for cleaning anytime



## SPECIFICATIONS



	416S	1040S	1870S		2180SR
Size	14 in / 350 mm	20 in / 500 mm	24 in / 600 mm	28 in / 700 mm	20 in / 500 mm
Battery voltage	24V (2 x 12)	24V (2x12)	24 V (2 x 12)	24 V (2 x 12)	24V (2 x 12)
Max up-to running time (mins)	70	180	140	140	140
Scrubbing width	14 in / 350 mm	20 in / 500 mm	24 in / 600 mm	28in / 700 mm	20 in / 500 mm
Brush speed	140 rpm	155 rpm	215 rpm	215 rpm	150 rpm
Maximum down pressure	55 lb / 25 kg	40 lb / 18 kg	67 lb / 30.5 kg	69 lb / 31.5 kg	48.5 lb / 22 kg
Scrub head raise/lower	n/a	Manual with foot pedal	Manual with foot pedal	Manual with foot pedal	Actuator
Brush motor	200 W	550 W	2 x 300 W	2 x 300 W	400 W
Theoretical productivity	12,936 ft <sup>2</sup> /hr 1,210 m <sup>2</sup> /hr	18,480 ft <sup>2</sup> /hr 1,730 m <sup>2</sup> /hr	27,456 ft <sup>2</sup> /hr 2,560 m <sup>2</sup> /hr	32,032 ft <sup>2</sup> /hr 2,990 m <sup>2</sup> /hr	32,560 ft <sup>2</sup> /hr 3,000 m <sup>2</sup> /hr
Solution tank capacity	4.2 g / 16 L	10 g / 40 L	18.5 gal / 70 L	18.5 gal / 70 L	20 g / 78.5 L
Recovery tank capacity	5 g / 19 L	13 g / 50 L	20 g / 75 L	20 g / 75 L	21 g / 80 L
Vacuum motor power	3 stage, 550 W	480 W	480 W	480 W	2 stage, 480 W
Squeegee width	17.7 in / 450 mm	32 in / 815 mm	32 in / 815 mm	39.7 in / 1,010 mm	28 in / 710 mm
Squeegee raise/lower	Hand lever	Hand lever	Hand lever	Hand lever	Actuator
Squeegee blade replacement	No-tool	No-tool	No-tool	No-tool	No-tool
Propel	Pad assist	Pad assist	Self-propel	Self-propel	Self-propel, foot pedal
Maximum speed	2.1 mph / 3.5 kmh	2.1 mph / 3.5 kmh	2.6 mph / 4.2 kmh	2.6 mph / 4.2 kmh	3.7 mph / 6.0 kmh
Maximum climbing angle	n/a	n/a	2%	2%	8%
Turning radius (wall to wall)	n/a	n/a	n/a	n/a	72.8 in / 1,851 mm
Dimensions (LxWxH)	30.9 x 18.4 x 45.8 in 787 x 468 x 1165 mm	48.4 x 20.3 x 37.8 in 1,230 x 516 x 960 mm	47.6 x 26.7 x 37.8 in 1,210 x 680 x 960 mm	48.0 x 29.4 x 37.8 in 1,220 x 748 x 960 mm	51.5 in / 26.5 x 40.5 in 1,310 x 673 x 1,030 mm
Weight (w/out battery)	79.3 lb / 36 kg	148 lb / 67 kg	206.5 lb / 93.7 kg	208.3 lb / 94.5 kg	260 lb / 118 Kg

### Want to place an order or have technical questions regarding a product?

Call 1-800-861-7352 or email [VLX-NA@tenantco.com](mailto:VLX-NA@tenantco.com). Visit [VLXclean.com](http://VLXclean.com) for machine set-up and operator videos.