



## M20 Specifications | Industrial Rider Sweeper-Scrubber

### INTEGRATED CLEANING SYSTEM

Cleaning path	40 in   1,020 mm
With scrubbing side brush	54 in   1,370 mm
With sweeping side brush	56 in   1,420 mm
Cylindrical main brushes	
Brush speed	480 rpm
Brush diameter (2)	12 in   300 mm
Brush down pressure (up to)	390 lb   177 kg
Side brush	
Brush speed	150 rpm
Brush diameter – scrubbing	16 in   410 mm
Brush diameter – sweeping	21 in   533 mm
Tanks	
Solution tank	56 gal   212 L
Solution capacity with ES®	74 gal   280 L
Recovery tank	73 gal   276 L
Demisting chamber	16 gal   61 L
Debris hopper	
Volume capacity	3.9 ft³   110 L
Weight capacity	390 lb   177 kg
Dump height (variable to)	60 in   1,520 mm
Vacuum fans	
Scrubbing fan speed	11,000 rpm
Scrubbing fan water lift	35 in   890 mm
Sweeping fan speed	6,500 rpm
Sweeping fan airflow	290 cfm   8.2 m³/min

### DUST CONTROL SYSTEM

Filter system	Synthetic fiber panel
Filter area	78 ft²   7.3 m²
Dust filtration (to)	3 microns @ 99% efficiency
Monitoring	Yes
Shaker mechanism (automatic)	Timed, beater bar
Wet sweeping	Integrated

### PROPELLING SYSTEM

Propel speed forward (variable up to)	8.0 mph   12.9 km/h
Propel speed reverse (variable up to)	3.0 mph   4.8 km/h
Engine - LPG (2.0 L)	42.4 hp   31.6 kW
Engine - diesel (1.5 L)	24.8 hp   18.5 kW
Gradeability	
Transport at gross weight	10.0 deg / 18.0%
Working (cleaning)	8.0 deg / 14%
Ground clearance (transport)	3 in   80 mm
Tire front (1), solid	18 x 5.5 in   460 x 140 mm
Tires rear (2), solid	16 x 3.5 in   410 x 90 mm

### MACHINE DIMENSIONS

Length	95 in   2,410 mm
Width	
Frame	50 in   1,270 mm
Rear squeegee	51 in   1,300 mm
With side brush	58 in   1,473 mm
Height	58 in   1,473 mm
With overhead guard	83.5 in   2,120 mm
Weight – empty	3,300 lb   1,497 kg
Minimum aisle turn	110 in   2,790 mm

### STANDARD FEATURES

1-Step™ one button sweep/scrub operation  
 Touch-n-Go™ wheel-mounted module  
 Wheel-mounted horn  
 Wheel-mounted water shut-off  
 No-tool squeegee change  
 No-tool brush change  
 Yellow maintenance touch points  
 Demisting chamber  
 Dual vacuum fans  
 Dura-Track™ parabolic rear squeegee  
 Cushion rollers  
 Fire extinguisher  
 SmartRelease™ breakaway squeegee system  
 FloorSmart® integrated cleaning system technology  
 Headlights and taillights  
 High-density Duramer™ exterior  
 InstantAccess™ filter change  
 MaxPro²™ hydraulic technology  
 Thermo-Sentry™  
 AV backup alarm (LED)  
 Edge cleaning – scrubbing or sweeping side brush

### OPTIONAL EQUIPMENT

Pro-Panel™ controls  
 ec-H2O™ solution system  
 ES® Extended Scrub w/detergent metering  
 Hopper cleanout tool  
 Overhead guard  
 Power wand  
 Vacuum wand (wet pick-up)  
 Safety warning light  
 Squeegee protection kit  
 Spray hose – 15 ft / 5 m  
 Pressure washer (2200 psi / 150 bar) with 25 ft (7.0 m) hose  
 IRIS® solution\*  
 \*Available in select regions

### WARRANTY

Please refer to your local Tennant representative for information.

For a complete selection of genuine Tennant brushes and pads, please consult the *M20 Parts and Consumables Reference Guide*.