

# MODEL S12 BATTERY POWER SWEEPER SPECIFICATIONS

S12BAT 05-05

## **KEY PRODUCT FEATURES**

Glide-In/Out Wheeled Hopper Instant Access Filter Color-Coded Wiring No-Tool Brush & Filter Change Corrosion-Proof Hopper & Shrouds Synthetic Panel Filter Non-marking tires 2 Built-In Utility Trays Low Effort Steering Removable shroud High Visibility Operation Decals Cup Holder Tool free Side Brush 360° Visibility Polyethylene Shrouds Battery Discharge Indicator

Retractable Side Brush Adjustable Recirculation Skirt Heavy Duty Motor Controller Hour Meter

## **SWEEPING SYSTEM**

Over Throw Type Coverage Rate per Hour Average (6.0 km/h, 15 cm overlap, one side brush) 4650 m<sup>2</sup> Maximum (full speed, no overlap, one side brush) 5580 m<sup>2</sup> Cleaning Path (one side brush) 900 mm Cleaning Path (two side brushes) 1100 mm Main Brush Length (Tubular) 700 mm Main Brush Lift Mechanical Lever Main Brush Drive Chain Side Brush Diameter (Disk) 405 mm Edge Cleaning Reach 90 mm Debris Access Clearance 95 mm Hopper Volume Capacity 85 L Hopper Weight Capacity 90 kg 0.4 kW **Brush Motor** 

# **DUST CONTROL SYSTEM**

Filter System Synthetic Panel Filter Filter Area  $4.5 \text{ m}^2$ Filter Seal Fail Safe Filter Seal Dust Filtration (to) Microns Mechanical Switch System Shaker Mechanism Vacuum Fan 0.3 kW Vacuum Fan Diameter 250 mm 3000 rpm Vacuum Fan Speed

#### PROPEL SYSTEM

Propel Motor 0.4 kW Gradeability Full Hopper  $8^{\circ}/14.1\%$  Gradeability Empty Hopper  $10^{\circ}/17.6\%$  Ground Clearance 65 mm Propel Speed

Forward (variable to)

Reverse (variable to)

6.2 km/h
4.5 km/h

Non-Marking Tires

1 Front, Solid 76 mm wide x 248 mm OD 2 Rear,Pneumatic 85 mm wide x 265 mm OD

#### **BATTERY & CHARGER**

Standard Capacity Battery Pack (4x6 Volt)

Fully Automatic "Smart" Charger

Runtime with 25 brush pattern on hard surface

Ca.4 hrs

#### SAFETY SYSTEM

Fire Protection Thermal Sentry Safety Certification CE Labeled Noise Level 72 dBa Key Switch Standard Power Shutdown Switch Standard Parking Brake Standard Seat Switch Standard Audio Backup Alarm and flashing light Standard

#### MACHINE DIMENSIONS

Length

Width 900 mm Height 1145 mm Weight Net 212 kg With  $180 \, \mathrm{AH^5}$  battery Package 332 kg

1435 mm

With 180 AH<sup>5</sup> battery Package 332 kg
Maximum Tire Footprint Pressure(with 180 AH<sup>5</sup> Batteries) 860 kPa
Minimum Aisle Turn 2210 mm

# **BRUSHES AVAILABLE (BRISTLE TYPES)**

Main BrushSide BrushSingle Row PolypropylenePolypropyleneDouble Row PolypropylenePolypropyleneCarpet – Natural FiberPolypropylene

#### MAJOR OPTIONAL EQUIPMENT

Left Hand Side Brush Foam filled rear tires

(Specifications subject to change without notice)