

V-DMU-14 | DUAL MOTOR UPRIGHT VACUUM



Delivering reliable performance and increased power at a lower total cost of ownership.

Reduce maintenance costs and downtime

The V-DMU-14 eliminates four key issues that cause vacuums to fail, thus increasing productivity and lowering service costs versus current commercial vacuums. Backed by a lifetime belt warranty, rest assured that this vacuum will be ready for action.

Reliable durability

Major components have been proven in commercial applications for over 10 years. This vacuum delivers high value at operating costs up to 58% less than many other commercial vacuums.*

Healthy, proven performance

Standard with HEPA 3-stage filtration, the vacuum's cleaning performance is also certified Silver by the Carpet and Rug Institute's (CRI) Seal of Approval program.

Maximizing versatility over single motor uprights, the powerful V-DMU-14 can clean multiple surfaces at the flip of a switch.

*Based on acquisition cost and assumed consumables (60 bags, 1 brush roll and 8 HEPA filters per year).

Key Product Features

- LEED qualifying with CRI SOA Silver performance and noise levels less than 70 dBA.
- Increase detailing productivity and cleaning coverage with on-board crevice and upholstery tools and up to 30% longer wand reach than the competition.
- Reduce maintenance costs and downtime with two cord strain reliefs for added cord protection.

V-DMU-14 | DUAL MOTOR UPRIGHT VACUUM



FEATURES	SPECIFICATIONS*
Product Name	V-DMU-14
Vacuum System Airflow at 2 in / 50 mm orifice Vacuum motor hp Vacuum motor type Vacuum motor watts/amps Water lift at sealed orifice	120 cfm / 3.4 m ³ /m 1.6 hp / 1.19 kW Single stage, thermal protected, clean air 1200 watts / 10 A 65 in/ 1650 mm
Brush Drive System Brush belt description Brush type Brush size Brush motor rating Brush height Brush RPM	PolyV lifetime belt Metal brush roll with natural bristles 12 in / 305 mm length 1.85A / 222W Automatic, self-adjusting 4250 RPM
Filtration Triple filtration system Triple filtration description Vacuum bag capacity	Filter bag, vac motor filter, and HEPA filter High efficiency (99.97%) at 0.3 micron Fill design, 3.8 qt / 3.6 L
Electrical Power cord length	50 ft / 15 m, 3 wire commercial safety-yellow cord with thermal protection switch
Chassis/Body Construction Construction	Injection molded ABS
Accessories Standard	On-board crevice tool, dusting brush with telescopic aluminum wand with 15 ft reach (4:1 stretch)
Dimensions / Weight / Sound Level Length Width Height Weight with cord Sound level (at operator's ear)	12.5 in / 320 mm 14.75 in / 370 mm 44 in / 1120 mm 24 lb / 11 kg < 70 dBA
Approvals	ETL, (US/C)
Warranty	See your sales representative or authorized distributor for complete warranty details.

*Specifications subject to change without notice

1100-108 V-DMU-14 Cut Sheet 09/11

The Tennant Company logo and other trademarks designated with the symbol "®" are registered in the United States and/or other countries. Tennant Company's products are sold and serviced through subsidiaries of Tennant Company and distributors.

Tennant
 701 North Lilac Drive
 Minneapolis, MN
 55422 USA

USA/Canada:
 +1.800.553.8033
 Quebec:
 +1.800.361.9050
 Overseas:
 +1.763.540.1315

www.tennantco.com
 info@tennantco.com