

Heavy Duty Upright Vacuum



A versatile heavy duty upright vacuum cleaner for everyday use.

Increase user comfort

The vacuum's spring-assisted design means lighter handle weight and less operator fatigue. The ergonomic handle is designed to fit every operator comfortably.

Robust performance

This upright vacuum is designed for years of use with its rotationally-molded base and robust foot latch. Three levels of filtration down to .1 micron at 99.99% efficiency help improve indoor air quality.

Productive product features

With variable height settings, this unit accommodates a variety of floor surfaces. Low profile capabilities allow the vacuum to lay flat to clean under hard to reach areas.



Key Benefits

- Rotationally-molded base is more durable than commonly used injected molded plastic
- Dual motor design with separate vacuum and brush motors deliver powerful, dirt-lifting suction
- Multi-signal indicator light alerts for product and user safety



Heavy Duty Upright Vacuum



Features	Specifications*	
Product Name	V-HDU-36	220 V
Vacuum System Airflow at 2 in / 50 mm orifice Vacuum motor hp Vacuum motor type Vacuum motor watts/amps Water lift at sealed orifice	125 cfm / 3.54 m ³ /h 1 hp / .75 kW each Through flow, single stage, thermal protected 915 watts / 7.9 A 80 in / 2030 mm	1 hp / .89 kW each 874 watts / 3.8 A
Brush Drive System Brush belt description Brush type Brush size Brush motor HP Brush motor RPM Brush RPM Brush height	Dual, round drive belts Single row, chevron pattern 2.25 in / 57 mm in diameter, 12 in / 305 mm length 0.1 hp / .07 kW 6000 3000 Adjustable to 6 positions with manual dial	
Filtration Triple filtration system Triple filtration description Vacuum bag capacity Vacuum hose length	Filter bag, vac motor filter, and post filter High efficiency (99.9%) at 0.3 micron Top fill design, 5.2 qt / 5 L 1.5 ft / 0.46 m (4:1 stretch ratio)	
Electrical Electrical system Indicator light Power cord length	Printed circuit board protected Multi - Signal light system for improved safety 40 ft / 12 m	
Chassis/Body Construction Construction	Rotationally-molded polyethylene	
Accessories Standard Optional	On-board crevice tool, swivel wand and flex hose Dusting brush, wall and upholstery tool	
Dimensions / Weight / Sound Level Length Width Height Weight Sound level (at operator's ear)	14.5 in / 368 mm 14 in / 356 mm 47 in / 1190 mm 21 lb / 9.53 kg 69.5 dBA	
Warranty	See your sales representative or authorized distributor for complete warranty details.	

*Specifications subject to change without notice Note: All 120V models will come with a dual Tennant/Nobles decal