



The 1040S is a reliable scrubber-dryer that delivers effective cleaning in small spaces. Its easy-to-maneuver design, intuitive controls and robust components provide for simple operation and maintenance. The 1040S is ideal for cleaning small, congested areas found in retail stores, hospitals and schools.



MANEUVERABLE, WITH EASY-TO-USE PAD ASSIST OR SELF-PROPEL OPERATION



ROBUST CONSTRUCTION IN A COMPACT SCRUBBER-DRYER



SOLUTION CONTROL WITH AUTOMATIC STOP



SELF-LEVELING BRUSH FOR MAXIMUM CLEANING PERFORMANCE



### **KEY FEATURES**



Intuitive control panel with electronic water flow control



Anti-foam system with vacuum motor protection



**Solution tank level gauge** and drain hose



Yellow touchpoints for easy daily maintenance



# **INSIDE THE**



- Control panel indicator light when solution tank level is low
- **2.** Large 40 L solution tank
- **3.** Easy-to-inspect in line solution filter
- Durable "V" shape squeegee assembly for consistent water pick-up
- Simple no-tools, no-touch brush change system
- Scrub deck cover made out of durable material



## **SPECIFICATIONS**

|                              | 500 mm Self-propel     | 500 mm Pad assist      |
|------------------------------|------------------------|------------------------|
| Voltage                      | 24V (2x12)             | 24V (2x12)             |
| Battery type                 | 105 Ah - GEL           | 105 Ah - GEL           |
| Max up-to running time (min) | 140                    | 150                    |
| Scrubbing width              | 500 mm                 | 500 mm                 |
| Brush speed                  | 155 rpm                | 155 rpm                |
| Maximum down pressure        | 18 kg                  | 18 kg                  |
| Scrub head raise/lower       | Manual with foot pedal | Manual with foot pedal |
| Brush motor                  | 550 W                  | 550 W                  |
| Theoretical productivity     | 2.250 m²/hr            | 1.750 m²/hr            |
| Solution tank capacity       | 40 L                   | 40 L                   |
| Recovery tank capacity       | 50 L                   | 50 L                   |
| Vacuum motor power           | 480 W                  | 480 W                  |
| Squeegee width               | 815 mm                 | 815 mm                 |
| Squeegee raise/lower         | Hand lever             | Hand lever             |
| Squeegee blade replacement   | No-tool                | No-tool                |
| Propel                       | Self-propel            | Pad assist             |
| Maximum speed                | 4,5 kmh                | 3,5 kmh                |
| Maximum climbing angle       | 2%                     | -                      |
| Dimensions (L x W x H)       | 1.230 x 516 x 960 mm   | 1.230 x 516 x 960 mm   |
| Weight (w/out battery)       | 73 kg                  | 67 kg                  |

## WARRANTY

12 months on parts and labour, excluding wear items, see your local representative for more information.