

Floor Scrubber-Dryers

Reliable floor scrubbers-dryers that offer a simple, straight-forward ownership experience at the right price.

416S

35CM MICRO WALK-BEHIND SCRUBBER-DRYER



Maneuverable to scrub in difficult to reach spaces



Simple and comfortable to operate



Large tank capacity in small size machine



1040S

50CM WALK-BEHIND SCRUBBER-DRYER



Maneuverable, with easy-to-use pad assist or self-propel operation



Solution control with automatic stop



Robust construction in a compact scrubber-dryer



Self-leveling brush for maximum cleaning performance



1870S

60/70CM WALK-BEHIND SCRUBBER-DRYER



Easy to maneuver with forward and reverse self-propel



Solution control with automatic stop



Durable construction in a mid-size scrubber-dryer



Self-leveling brush with high RPM for maximum cleaning efficiency



2180SR

50/60CM MICRO-RIDER FLOOR SCRUBBER-DRYER



Quickly reach many areas of a facility with a ride-on scrubber-dryer



Compact design easily fits into most congested areas



Simple to operate control panel with visual display



Quiet operation allows for cleaning anytime



SPECIFICATIONS



| | 416S | 1040S | | 1870S | | 2180SR | |
|-------------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|
| Scrubbing width | 350 mm | 500 mm | | 600 mm | 700 mm | 500 mm | 600 mm |
| Battery voltage | 24V (2 x 12) | 24 V (2x12) | | 24 V (2 x 12) | | 24 V (2 x 12) | 24 V (4 x 6) |
| Battery type | 29 Ah - AGM | 105 Ah - GEL | | 105 Ah - GEL | | 105 Ah - GEL | 180 Ah - GEL |
| Max up-to running time (mins) | 70 | 140 | | 125 | | 150 | 210 |
| Brush speed | 140 rpm | 155 rpm | | 215 rpm | | 150 rpm | 220 rpm |
| Maximum down pressure | 25 kg | 18 kg | | 30,5 kg | 31,5 kg | 22 kg | 50 kg |
| Scrub head raise/lower | n/a | Manual with foot pedal | | Manual with foot pedal | | Actuator | |
| Brush motor | 200 W | 550 W | | 2 x 300 W | | 400 W | |
| Theoretical productivity | 1.300 m ² /hr | 2.250 m ² /hr | 1.750 m ² /hr | 2.579 m ² /hr | 2.848 m ² /hr | 3.180 m ² /hr | 3.684 m ² /hr |
| Solution tank capacity | 16 L | 40 L | | 70 L | | 78,5 L | |
| Recovery tank capacity | 19 L | 50 L | | 75 L | | 80 L | |
| Vacuum motor power | 3 stage, 550 W | 480 W | | 480 W | | 2 stage, 480 W | 3 stage, 550 W |
| Squeegee width | 450 mm | 815 mm | | 815 mm | 1.010 mm | 710 mm | 942 mm |
| Squeegee raise/lower | Hand lever | Hand lever | | Hand lever | | Actuator | |
| Squeegee blade replacement | No-tool | No-tool | | No-tool | | No-tool | |
| Propel | Pad assist | Self-propel | Pad assist | Self-propel | | Self-propel, foot pedal | |
| Maximum speed | 3,5 km/h | 4,5 km/h | 3,5 km/h | 4,2 km/h | | 6 km/h | |
| Maximum climbing angle | n/a | 2% | - | 2% | | 8% | 16% |
| Turning radius (wall to wall) | n/a | - | | - | | 1.851 mm | 1.853 mm |
| Dimensions (LxWxH) | 787 x 468 x 1.165 mm | 1.230 x 516 x 960 mm | | 1.210 x 680 x 960 mm | 1.220 x 748 x 960 mm | 1.310 x 673 x 1.030 mm | |
| Weight (w/out battery) | 36 kg | 73 kg | 67 kg | 93,7 kg | 94,5 kg | 118 kg | 134 kg |

WARRANTY

12 months on parts and labour, excluding wear items, see your local representative for more information.